

CCL



IP PHONE

IPH-22

Enterprise Entry Level
Business Phone and HD Audio

IPH-22

Key Features

- HD Voice
- 2 SIP Accounts
- 2 Line keys
- 5-way Conference
- 132x64 pixel Graphical LCD with Backlight
- Dual-port 10/100Mbps Ethernet
- Support EHS wireless headset (Plantronics, Jabra, Sennheiser)
- Stand with 2 adjustable angles
- Full Compatible with 3CX, Asterisk, Yeastar, Xorcom, VoIP.ms, Broadsoft, Free SWITCH Platform etc.



HD Voice



2 SIP Accounts



2 Line Keys



2.3" Graphic LCD



5-way Conference



PoE

Model	Screen	Network	PoE Support	Power Adapter
IPH-22	132x64"	2*10/100M	x	Optional

Rich visual Experience

The IPH-22 is an entry-level IP Phone, which can be applied to various IP Voice Phone systems. The IPH-22 not only integrates a 132x64 pixel graphic LCD and an elegant and intuitive user interface, but also supports high-definition voice calls and other calling functions, which can fully meet the needs of users in various industries.

High Quality Audio

The full duplex speaker and microphone system and the Digital Signal Processor (DSP) ensure that the IPH-22 delivers high audio quality. Whether you use the hands-free speakerphone or the handset, you will always have good experience and crystal-clear call quality.

Call Features

- 2 SIP Accounts
- Call Waiting
- Call Forward
- Blind/attended transfer
- Call hold, Call mute, DND mode
- Speed Dialing, Hotline
- Redial, Call Return
- Auto-redial, Auto-answer
- Dial Plan
- 5-way conference
- Peer Dialing

Phone Features

- Adjustable Voice Volume
- Selectable Ring Tones
- XML Browser
- Action URL/URI
- Keyboard lock
- Programmable DSS keys
- Phonebook: 1,000 Groups
- Blacklist: 100 Groups
- Call Log: 100 Logs
- Support 5 Remote Phonebook URLs
- LDAP
- Support Multiple Languages
- Support EHS wireless headset (Plantronics, Jabra, Sennheiser)

Management

- Auto provisioning:
 - FTP/TFTP/HTTP/HTTPS/PnP
- Configuration via HTTP/HTTPS web
- SNMP, TR069
- Network capture
- NTP/Daylight saving time
- Firmware upgrade via web
- Syslog
- Configuration backup/restore
- Equipment Management System (NMS)

IP-PBX Features

- SMS, Voicemail, MWI
- Music On-hold, Intercom, Multicast
- Call Pickup, Call Pickup in Group
- Anonymous Call
- Anonymous Call Rejection

Audio

- HD Voice
- Wideband Codec: G.722, OPUS-WB
- Narrowband Codec: PCMA, PCMU, G.729, G723, G726, AMR, OPUS, iLBC
- Echo Cancellation/Dynamic Jitter
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Full-duplex Speaker

Protocols & Standards

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- SIP over TLS, SRTP
- TCP/IP/UDP
- RTP/RTCP, RFC2198, RFC1889
- HTTP/HTTPS/FTP/TFTP
- ARP/RARP/ICMP/NTP/DHCP
- DNS SRV/ A Query/NATPR Query
- STUN, Session Timer (RFC4028)
- DTMF: In-Band, RFC2833, SIP INFO
- LLDP
- OpenVPN, 802.1X

Physical Features

- 132x64 pixel graphic LCD with backlight
- Dual-angle foot stand: 40° and 45°
- Dimensions(approx.):
 - 180x192x36mm(WxLxD) without foot stand
- Weight(approx.): device 370g, foot stand 60g
- Power supply: 5Vdc power adapter
- Power consumption: 1.4W
- Handset: 4P4C, RJ9
- Headset: 4P4C, RJ9
- Environmental conditions:
 - Operation temperature: 0~40°C
 - Humidity: 10% to 95% (non-condensing)
- 2xRJ45 10/100M Ethernet Ports
- Wall Mountable